Data sheet



Cable attachment kit w.a two-way circuit

Material no.: 1000002079 | Matchcode: EL AK WS | EAN code: 4045294234881



- » universal cable kit
- » LED Light two way switch
- 8 Meter FLYY 2 x 0.75 mm²
- 3 10 Meter FLYY 1 x 1.5 mm²
- Fuse holder floor mounting with 3 A auto plug-in fuse ATO

| ١ | Λ | a | te | П | a | s | & | C | o | 0 | u | r |
|---|---|---|----|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | |

Colour: Black

Dimensions

Outer dimensions: 330 x 210 x 55 mm

Technical data

Weight: 0,69 kg
Voltage in volts: 10-30 DC

Conformity

EMC Compliant: No

Accessories

Material no. Description Matchcode EAN code



801014906 12 V on/off switch with orange indicator light ZEASO 4045294165314



Cable attachment kit w.a two-way circuit

Material no.: 1000002079 | Matchcode: EL AK WS | EAN code: 4045294234881

| | Material no. | Description | Matchcode | EAN code |
|---|--------------|---|-----------------|---------------|
| 2 | 6000002918 | On/Off switch with round orange indicator light | EL WS ON/OFF OR | 4045294431600 |
| | 6000000710 | Two-way switch round on/on | EL WS ON/ON | 4045294209810 |
| 0 | 6000001305 | Switch taperound D=20 | EL AK S | 4045294226282 |

Description

The cable attachment kit with a two-way circuit is a universal cable kit for realising a two-way circuit for the lighting in your vehicle. The switch can be installed both on the rear door as well as in front on the sliding doors. Cable lengths sufficient for vehicle of length L2. This kit can also be used as a universal cable kit for warning beacons. The contents of a cable attachment kit for two way switch in detail:

- 8 Meter vehicle cables FLYY 2 x 0.75 mm²
- 10 Meter vehicle cables FLYY 1 x 1.5 mm²
- 1 fuse holder ATO floor mounting
- 1 flat plug fuse 3A ATO purple
- 1 Ring connector for pins M6 0.5 1.5 mm² red
- 2 push on receptacles fully insulated 1.5 2.5 mm² 6.3 mm blue
- 2 through connectors $0.5 1.0 \text{ mm}^2 \text{ red}$
- 4 push on receptacles fully insulated 0.5 1.0 mm² 4.8 mm red
- 2 push on receptacles fully insulated 1.5 2.5 mm² 4.8 mm blue

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 21.12.2023