

LED beacon yellow ,10-30 V plug socket

Material no.: 6000002370 | Matchcode: LED KL G STSO | EAN code: 4045294269487



- » suitable for plug base form A Ø 24 mm acc. to DIN 72591
- » simple plugging-in when required
- » Registration complying with ECE R65 & ECE R10-04
- » Operating voltage 10-30 VDC
- » protection class IP 67

Dimensions

Outer dimensions: 150 x 150 x 235 mm

Technical data

Weight: 0,70 kg

IP Protection: 67

Voltage in volts: 12
24

Conformity

EMC Compliant: Yes

ECE mark: E4 R65
E4 10R-04

Accessories

	Material no.	Description	Matchcode	EAN code
	1000005392	Warning beacon plug base holder for side rails	STS 2.0 KLS S WA	4045294531218

LED beacon yellow ,10-30 V plug socket

Material no.: 6000002370 | Matchcode: LED KL G STSO | EAN code: 4045294269487

	Material no.	Description	Matchcode	EAN code
	1000005393	Warning beacon plug base holder for cross members	STS 2.0 KLS S QT	4045294531225
	1000002178	warning labels set for vehicles DIN 30710	WAMA FZS DIN 30710	4045294237202

Description

This LED beacon is suitable for plug base form A Ø 24 mm acc. to DIN 72591. The lights can therefore be simply plugged-in to a fixed base on the vehicle or a telescopic mast when required. The yellow flashing light is used for warnings about danger.

You can operate the lights with an operating voltage of 10-30 VDC. Additionally the warning beacons conform to ECE R65 E04 006598 as well as ECE R10-04 and thanks to the LED technology are extremely long-lasting.

The lights emit 120 double flashes per minute. Thanks to its protection class IP 67 and a temperature range of -40 to +70 °C, it is ideally suited for operations outdoors.

The height is 198 mm, the diameter is 149 mm.

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 21.12.2023